



Set up the LEICA Disto S910

- Mount the Leica Disto S910 on the tripod mount and the tripod
- Place the tripod on a position on stage where you are able to reach the origin, the X+ axis mark and as many anchors and cp calibration points as possible with the laser.
- Level the tripod
- Turn ON the Leica Disto S910 and open up a WIFI Hotspot on the Leica Disto S910
- Press FUNC on the Leica Disto S910
- Tap  in the right bottom corner and press = on the keyboard
Note: If the Leica Disto S910 is connected correctly, the Leica calibration will start automatically now.
- Level the Leica Disto S910

- Connect the tablet to the Leica WIFI Hotspot
- Open the zacktrack APP on the zacktrack tablet
- Go to *Show Editor* and tap Points on the bottom
- Tap Disto Status
- Tap Discover to get the current ip address of the Leica S910 Disto and tap Ok
- The Leica Disto S910 is now ready for measuring

RELATED TOPICS

- [Define origin on stage](#)
- [Relocate measuring tool](#)
- [Validate Points](#)
- [Measure Points](#)

From:
<https://manual.zacktrack.com/> - **zacktrack**

Permanent link:
https://manual.zacktrack.com/doku.php?id=pro:set_up_the_leica_disto

Last update: **2020/04/20 10:24**

