

DISCOVERY

Before you can measure your anchors and calibrate your system, you have to discovery your anchors and trackers.

- Tap on the 3 dots in top right corner to open the menu (see [Menu](#) for details).
- Tap on the option **Tracking Server**.
- With the dialog popping up, you can discovery your anchors and trackers.



- Tap on the button **Discover Devices** to discover your trackers.
- Follow the instructions displayed in the wizard.
 - Turn on the anchors and tap *Next*.
 - Put the trackers you want to discover into the charging station. Make sure a USB-C cable is plugged into the charging station. The LED of the trackers you put in the charging station should either blink red or emit a constant green light.
 - Take the trackers out of the charging station after a few seconds and place them near the master anchor.
 1. The system can now discover the trackers within three minutes after you took them out of the charging station.
 2. Tap *Next* to discover the trackers.



The system tries to discover the anchors and trackers now.



- The system has finished the discovery process.
- The dialog will show you now how many unassigned trackers it discovered.

Note: Trackers that are already part of your show/configuration are not counted here.



- You have finished the discovery process of your anchors and trackers.
- You will return to the screen displayed in the first image on this page.
- Make sure that the system discovered all of your anchors and trackers.
- Make sure that all of your trackers and anchors have a correct firmware version.

Anchor is missing

If anchors are missing make sure that:

- you have switched them on (a LED should emit some light at the front of the anchor, and another one at the back).
- your anchors are charged. You can charged them with a USB-C cable at the back.
- your anchors are not blocked by other thing, e.g., fixtures, trusses, etc.

Tracker is missing

If trackers are missing make sure that:

- your trackers are charged. You can charged them with the charging station.
- your trackers are near the Master anchor during the discovery.
- nothing is in the Line-of-Sight between your trackers and the Master anchor.

Anchor Firmware invalid

- Tap on *Anchors* above the list displayed in the screen.
- Tap on the orange text *fw invalid*.
- Tap on the button **Update selected** to update the firmware of your anchors.

Tracker Firmware invalid

- Tap on *Trackers* above the list displayed in the screen.
- Tap on the orange text *fw invalid*.
- Tap on the button **Update selected** to update the firmware of your trackers.

From:

<https://manual.zacktrack.com/> - **zacktrack**

Permanent link:

https://manual.zacktrack.com/doku.php?id=manual:mini_discovery

Last update: **2022/11/04 14:10**

